

## TD.432 – TECHNICAL DATA: THIN-FINISH™

Product Name: THIN-FINISH™ Overlay – Part of the Pre-Mixed Overlay System

Product Class: Dry, Redispersible, Cement based Mortar

### Use Applications:

- For thin surface repairs and resurfacing of concrete substrates
- For creating splatter/hoppergun applications, knockdowns, base/skim coats, broom finishes, seamless interior flooring, stenciled cement and more
- For creating repair and patching mixes for concrete surfaces

### Key Features:

- Better overall performance than most other resins, modifiers and polymers, including: Acrylic, polyvinyl acetate, styrene and silicone
- Provides a permanent bond (with correct substrate preparation on stable concrete surfaces above grade)
- Increased levels of finishes moisture resistance, flexural and tensile strengths
- Increased texturing capabilities
- Exceptionally long pot life
- Increase versatility and application range
- Can be colored with PORTION CONTROL COLORANT™ for custom coloring
- Can be colored with SYPP – Synthetic Primary Pigment for custom coloring
- Can be colored with ULTRA-STONE™ Antiquing Stain for custom coloring

### Product Properties:

- Appearance – Fine Powder
- Smell – N/A
- Nonvolatile Content % - N/A
- GT Temperature – N/A
- Flammability - N/A
- Weight, Lb. Per stock container – 55 lbs.
- Application temperature - 40° - 100° F
- Cured:
  - 70% - 7 days @ 70° F
  - 100% - 28 days
- Resistance to moisture deterioration - Excellent
- Resistance to weather, including UV and freeze/thaw cycles - Excellent

### Available Packaging:

- Stock – 55 lbs. bags, 56 bags per pallet
- Available in White and Gray
- Special Order - Inquire

### Suggested Storage:

- Keep Dry
- Shelf Life - 6 months to a year